

Technical Data Sheet M-Series

Basic Info

KSF M 76x3,6x2100 M16 HDG	KSF M 76x3,6x1600 M16 HDG	KSF M 76x3,6x1300 M16 HDG
Nominal length (mm)		
2100	1600	1300
Tube diameter (mm)		
76,10	76,10	76,10
Weight (kg)		
16	12	10
Item number		
A0447	A0445	A0443

Construction

- Flange: Sheet metal S355
- Coating: Hot-dip galvanized according to DIN EN ISO 1461
- Continuous welded helix

Applications



KSF M 76x3,6x1600 M16
HDG



sustainable · durable · revolutionary

Technical Data

	KSF M 76x3,6x2100 M16 HDG	KSF M 76x3,6x1600 M16 HDG	KSF M 76x3,6x1300 M16 HDG
a	Length (mm) (± 25 mm)		
	2070	1570	1270
b	Shaft outer diameter (mm)		
	76,10	76,10	76,10
c	Inner diameter (mm)		
	68,90	68,90	68,90
d	Thread (mm)		
	M16	M16	M16
e	Pitch circle diameter (mm)		
	150	150	150
f	Pitch circle holes (mm)		
	6 x \emptyset 14	6 x \emptyset 14	6 x \emptyset 14
g	Flange wrench size (mm)		
	166	166	166
h	Flange outer diameter (mm)		
	182	182	182
i	Flange thickness (mm)		
	10	10	10
j	Thread length (mm)		
	1150	850	750

