

Technical Data Sheet U Series

Basic info

| KSF U 60x2,0x730-71HDG | KSF U 60x2,0x550-71 HDG |
|------------------------|-------------------------|
| Nominal length (mm) | 550 |
| 730 | |
| Tube diameter (mm) | 60 |
| 60 | |
| Weight (kg) | 2.10 |
| 2.60 | |
| Item number | A0456 |
| A0458 | |



Construction

- Coating: Hot-dip galvanized according to DIN EN ISO 1461
- Continuous welded helix
- Patented conical body forged from a single piece of tubing

Applications



KSF U 60x2,0x730-71 HDG

Accessories



Screw-in bar short

Art.-Nr. A0133

Technical Data

| | KSF U 60x2,0x730-71HDG | KSF U 60x2,0x550-71 HDG |
|---|---------------------------------------|-------------------------|
| a | Length (mm) (± 25 mm) 730 | 550 |
| b | Shaft outer diameter (mm) 60 | 60 |
| c | Square hole spacing (mm) 42 | 42 |
| d | Middle square hole spacing (mm) 94 | 94 |
| e | Square hole spacing (mm) 50 | 50 |
| f | Square hole diameter* (mm) 11 | 11 |
| g | Gauge (mm) 71 | 71 |
| h | U profile width (mm) 70 | 70 |
| i | U profile depth (mm) 134 | 134 |

* to fit M10 carriage bolts

